



### RIBBON CURB

**NOTES:**

1. CONCRETE COMPRESSIVE STRENGTH SHALL BE 3600 P.S.I. IN 28 DAYS.
2. EXPANSION JOINTS AS FOLLOW:
  - 2.1 1/2 INCH THICK
  - 2.2 MAXIMUM SPACING OF 100 FT
  - 2.2 MINIMUM SPACING OF 50 FT
  - 2.3 RUBBERIZED EXPANSION JOINT FILLER (ASSHTO M153, TYPE 1)
  - 2.4 POLYPROPYLENE FOAM JOINT FILLER (ASTM D8139)
3. CONTRACTION JOINTS AS FOLLOW:
  - 3.1 MAXIMUM SPACING OF 10 FT
  - 3.2 MINIMUM SPACING OF 6 FT
  - 3.3 1/4 INCH DEPTH, EITHER SAWCUT OR HAND GROOVED
4. PRIOR APPROVAL FROM THE DIRECTOR OF ENGINEERING IS REQUIRED FOR USE OF THIS TYPE OF CURB



**TOWN OF INDIAN TRAIL  
STANDARD DETAIL**

**RIBBON CURB**

REVISIONS	Scale Not To Scale
	Revision Date 01/2025
	Detail # T_4.03